



FTM 181

Airport Lighting Monitor



The FTM 181 approach lighting monitor is used with the FTS 430 and 830 series of current-driven airport approach lighting.

The FTM 181 communicates with the lighting units and displays their flashing status. It is programmed to show SSALR and ALSF-2 operation of the sequential lights.

The FTM 181 provides a set of isolated relay contacts representing each light to be used for telemetry. The contacts open to indicate a failed light.

FEATURES & BENEFITS

- LED indicators for onsite at-a-glance status
- Independent LED status indicator for each light
- 15 individual dry contacts & 1 system dry contact
- Option for normally open or normally closed data point
- NEMA 4X stainless steel outdoor rated enclosure

SPECIFICATIONS

- 19 x 18.8 x 6" (482.6 x 477.5 x 152.4 mm)
- Environmental: -50 to +55 degrees C

FTC 181

This page intentionally left blank.



Bright Ideas. Brilliant Results.

Flash Technology
332 Nichol Mill Lane
Franklin, TN 37067-8203 USA

T +1 615 503 2000

T +1 888 313 5274

F +1 615 261 2600

flashtechnology.com



ISO 9001:2015

D1810-01 Rev C

*Data and specifications subject to change
without notification.*

©2018 Flash Technology
All rights reserved.



SPX

SPX Corporation
**Global Industrial Equipment
& Global Manufacturing**
spx.com