





FT 723 Airport Acquisition Beacon



Designed to assist airport acquisition by pilots flying in the vicinity, Flash Technology's FT 723 airport beacon is an omnidirectional xenon beacon that emits an intense, flashing white light. Utilizing no moving parts, the FT 723 minimizes installation, operation and maintenance costs.

MAINTENANCE

- An extensive instruction manual and drawings are provided with each system.
- Trained technical support staff and information on support programs are readily available through our National Operations Center (NOC) services department.
- Onsite training through Flash University is also available.

FT 723

GENERAL SPECIFICATIONS

Flashhead - FH 308	
Dimensions	18.25" x 17" (463.6 mm x 431.8 mm)
Weight	17 lbs. (7.7 kg)
Effective Candela	12,000 ± 25% ECD - white day 6,000 ± 25% ECD - white twilight 2,000 ± 25% ECD - white night
Aerodynamic Wind Area	0.93 ft² (0.0864 m²)
Vertical Beam	5°
Horizontal Coverage	360°
Flashes per Minute	20 fpm

Power Converter - PC 723	
Power Consumption	130 watts
Input Voltage	120, 208 or 240 volt 60 Hz 230 volt 50 Hz Single phase (specify on order)

Status relays with form C contacts



Bright Ideas. Brilliant Results.

Flash Technology 332 Nichol Mill Lane Franklin, TN 37067-8203 USA

T +1 615 503 2000 T +1 888 313 5274 F +1 615 261 2600

flashtechnology.com



D7230-01 Rev B

Data and specifications subject to change without notification.

©2018 Flash Technology All rights reserved.



SPX Corporation
Global Industrial Equipment
& Global Manufacturing
spx.com