

LED ENHANCED SIGNS

High-intensity LED enhanced signs for crosswalks, school zones, warning, and stop signs

- Signs operate independently or can supplement RRFBs and beacons
- High intensity flashing increases driver compliance
- Compact, lightweight design to simplify installation
- Programmable for pedestrian activation, calendar function, or 24/7 operation
- Proven technology platform
- Meets and exceeds MUTCD requirements

High-Intensity Light Output

Our LED Enhanced Sign provides high intensity light output that can improve driver response under all conditions, no matter the time of day or weather. Our signs are MUTCD compliant, install quickly, and can be powered by any Carmanah solar or AC system.

Easy Installation

With its highly efficient and compact design, installation is quick and uncomplicated, dramatically reducing installation costs. Retrofitting can be done where existing sign bases are used to enhance existing sites in minutes, and new installations can be completed without the cost of larger poles, new bases, and trenching.

Advanced User-Interface

Our LED Enhanced Sign comes with an on-board user interface for quick configuration and status monitoring. It allows for simple in-the-field adjustment of flash pattern, duration, intensity, ambient auto adjust, night dimming, and many more. Optional manual override switch or wireless connection for local or remote control.

Reliable

Designed with Carmanah's industry-leading solar modeling tools to provide dependable year-after-year operation.

Trusted

With thousands of installations, Carmanah's beacons are the benchmark in traffic applications and other transportation applications worldwide.




WE SIMPLIFY PLANNING.

Contact us to get your Energy Balance Report and purchase specifications.

 1.844.412.8395

 traffic@carmanah.com

 carmanahtraffic.com

LED ENHANCED SIGNS



REGULATORY SIGNS



R1-1

MUTCD Chapter 2B compliant, R1-1 layout
3M Diamond Grade DG3 retroreflective sheeting, 4092 red
8 red LEDs
24, 30, 36, and 48" sign sizes

WARNING SIGNS



W11-2

MUTCD Chapter 2C compliant, W11-2 layout
3M Diamond Grade DG3 retroreflective sheeting, 4081 fluorescent yellow
8 yellow LEDs
24, 30, 36, and 48" sign sizes

SCHOOL SIGNS



S1-1

MUTCD Chapter 7B compliant, S1-1 layout
3M Diamond Grade DG3 retroreflective sheeting, 4083 fluorescent yellow green
8 yellow LEDs
30, 36, and 48" sign sizes

OTHER SIGNS AVAILABLE



W1-2
Yellow



S5-1
Yellow



R1-2
Red




R5-1a
Red




On-Board User Interface (OBU)	Adjustable system settings with auto-scrolling LED display on our latest EMS
	System test, status, and fault detection: battery, solar, button, beacon, radio, day/night
	Flash patterns: RFB1 (WW+S), RFB2 (WSDOT), 0.5 sec. alternating (MUTCD), 0.5 sec. unison (MUTCD), 0.1 sec. unison, 0.25 sec. unison, 0.1 sec. x3 quick flashes unison, 0.1 sec. x3 quick flashes alternating
	Input: momentary for push button activation, normally open switch, normally closed switch
	Flash duration: 5 sec. to 1 hr.
	Intensity setting: 20 to 1400 mA for multiple LED enhanced signs
	Nighttime dimming: 10 to 100% of daytime intensity
	Ambient Auto Adjust: increases intensity during bright daytime
	Automatic Light Control: reduces intensity if the battery is extremely low
	Temperature correction: yellow or red LED enhanced signs
Sign Construction	Calendar: internal time clock function
	Radio settings: enable/disable, selectable channel from 1 to 14
	Output: enabled when flashing daytime and nighttime, or nighttime only
	Activation counts and data reporting via OBU or optional USB connection
	MUTCD compliant: 2009 MUTCD, Chapter 2A, 2B, 2C, and 7B Signs
	High-power LEDs in waterproof housings
	Aluminum channels protect wiring; includes junction box
	0.08-0.10" aluminum sign face with stainless steel hardware
	Optional encrypted, wireless radio with 2.4 GHz mesh technology
	Optional radio allows calendar program, manual override switch, or input device from one system to remotely control other systems
Connectivity	User-selectable multiple channels to group different signs and ensure a robust wireless signal
	Instantaneous wireless activation: <150 ms
	Wireless range: 1000 ft (305 m)
Power System	Integrated, vandal-proof antenna
	Solar or AC-powered
Energy Collection	AC: 90-264 VAC input, 6-14 AWG
	Replaceable AC-DC power supply, circuit breaker, terminal block wiring
Energy Storage	45 deg tilt for optimal energy collection
	Maximum Power Point Tracking with Temperature Compensation (MPPT-TC) battery charger for optimal energy collection in all solar and battery conditions
Solar Engine Construction	Replaceable, recyclable, sealed, maintenance-free, best-in-class AGM batteries offer the widest temperature range and longest life
	Battery design life: +5 yrs.
Environmental	Tool-less battery change with quick connect terminals and strapping for easy installation
	Weatherproof, gasketed enclosure with vents for ambient air transfer (NEMA 3R)
	Lockable, hinged enclosure for access to on-board user interface and batteries
Warranty	Corrosion-resistant aluminum with stainless steel hardware
	Raw aluminum finish or yellow, black, or green powder coated
	Prewired to minimize installation time
	High-efficiency optics and EMS = the most compact, lightweight system
	-40 to 165° F (-40 to 74° C) system operating temperature
	-40 to 140° F (-40 to 60° C) battery operating temperature
	5-year limited warranty on power options
	3-year limited warranty on signs

POWER OPTIONS



E Series
Compact, integrated solar engine



F Series
Larger, integrated solar engine



G Series
Cabinet-based solar and AC systems

Specifications subject to local environmental conditions, and may be subject to change.

All Carmanah products are manufactured in facilities that are certified to ISO quality standards.

US Patent No 6,573,659, Other patents pending.

"Carmanah" and Carmanah logo are trademarks of Carmanah Technologies Corp.

© 2018, Carmanah Technologies Corp.

Document: SPEC_TRAF_LED-enhanced-signs_RevA